

The KHT MultiScan

Mobile master data recording station for article dimensions and weights
MultiScan 600 • MultiScan 800 • MultiScan 1200

Technical data

	MultiScan 600	MultiScan 800	MultiScan 1200
Equipment dimensions without accessories (LxWxH)	1120 x 775 x 725 mm 44 x 30.5 x 28.5 inch	1320 x 775 x 725 mm 51.9 x 30.5 x 28.5 inch	1720 x 775 x 725 mm 67.7 x 30.5 x 28.5 inch
Length measuring range	3 – 600 mm 0.11 – 23.62 inch	3 – 800 mm 0.11 – 31.49 inch	3 – 1200 mm 0.11 – 47.24 inch
Width measuring range	3 – 640 mm 0.11 – 25.19 inch	3 – 640 mm 0.11 – 25.19 inch	3 – 640 mm 0.11 – 25.19 inch
Height measuring range	3 – 470 mm 0.11 – 18.5 inch	3 – 470 mm 0.11 – 18.5 inch	3 – 470 mm 0.11 – 18.5 inch
Indication increment	1 mm 0.03 inch	1 mm 0.03 inch	1 mm 0.03 inch
max. absolute measurement deviation	+ 2,5 mm ¹ + 0.09 inch ¹	+ 2,5 mm ¹ + 0.09 inch ¹	+ 2,5 mm ¹ + 0.09 inch ¹
Weight measuring range	5 – 40000 g 0.17 – 1,410.95 oz	5 – 40000 g 0.17 – 1,410.95 oz	5 – 40000 g 0.17 – 1,410.95 oz
Indication increment	1 g 0.03 oz	1 g 0.03 oz	1 g 0.03 oz
max. absolute measurement deviation	+/- 3 g +/- 0.10 oz	+/- 3 g +/- 0.10 oz	+/- 3 g +/- 0.10 oz
Interfaces	PC keyboard emulation ² CSV file alternatively via USB or in Network ³ Serial RS232 XML protocol over TCP/IP Webservice/REST		

1 – Dependent on the measurement mode; 2 – DataFlowController is required; 3 – Software DataScan is required

KHT GmbH

Uferstraße 10
45881 Gelsenkirchen

Fon: +49 (0) 209 94 11 70
Fax: +49 (0) 209 94 11 717

info@kht.de
www.kht.de

