

Accessories

- _ transport trolley
- _ barcode reader
- _ industrial camera
- _ Touch PC with software
- _ label printer

DataScan Software

The extension of the DataScan software creates, if needed, a complete master data acquisition system with a direct interface to the merchandise management system. From parameterizable languages, units and acquisition fields, the software can be adapted at any time without touching existing interfaces.

CartonScan technical data

The KHT service package

- _ On-site training
- _ On request: Service and maintenance contracts
- _ software can be remotely maintained

	CartonScan 600	CartonScan 800
Device dimensions without accessories	68 x 68 x 113 cm 26.8 x 26.8 x 44.5 in	88 x 88 x 113 cm 34.6 x 34.6 x 44.5 in
Weight without accessories	15,6 kg / 34.4 lbs	17 kg / 37.5 lbs
Minimum measurable article dimensions	4 x 4 x 2 cm 1.5 x 1.5 x 0.8 in	4 x 4 x 2 cm 1.5 x 1.5 x 0.8 in
Maximum measurable article dimensions	62 x 62 x 94 cm 24 x 24 x 37 in	82 x 82 x 94 cm 32 x 32 x 37 in
Minimum measurable article weight	0,05 kg / 0.11 lbs	0,05 kg / 0.11 lbs
maximum article weight	55 kg / 120 lbs	55 kg / 120 lbs
Power supply	100-240 VAC	
Dimensioning technology	Ultrasonic	
Weighing technology	4 x load cell	
interfaces	CSV / XML / HTTP	
User interface	Windows	
Permissible operating temperature	+15 to +30°C / +59 to +86°F	
Accessories	transport trolley, barcode reader, label printer, camera	
Touch PC	ICO Touch PC & DataScan application	